

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15

71711 Steinheim

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

**FLEX**

## Screwing and drilling

### CHE 5-45 SDS-max

Order no. 365.912

**Universal rotary hammer drill, 5 kg, SDS-max**

- Handy L-design 1100 watt rotary hammer drill and chisel hammer
- Hammer drilling
- Rotation stop for chiselling
- Max. drilling range: up to 45 mm with hammer drill, 80 mm drilling with a core drill, 90 mm drilling with carbide metal drill bit
- With a variable speed setting for optimum speed depending on requirement and tool
- With supplementary handgrip and vibration-dampened handle
- Ideal for hammer-drilling, diameter 10-32 mm in masonry and concrete for composite or injection anchoring systems and through-holes
- Suitable for light-duty chiselling work to remove plaster, masonry and lightweight concrete
- The integrated service display indicates the next change for carbon brushes as well as the service interval

Technical attributes	CHE 5-45 SDS-max
No load speed	235-500 rpm
Blows per minute	1350-2870 bpm
Single impact energy (EPTA)	7,1 J
Chisel positions	12
Max. drill hole Ø in concrete	45 mm
Max. drill hole Ø in masonry (drill bit)	105 mm
Power input	1100 watt
Tool fixture	SDS-max
Weight	5,9 kg

Standard equipment
1 drill depth stop
1 handle
1 tube of grease
Carry case